



**SPECIFICATION:**

- 1.Connector:LC/PC-ST/PC MM/Ø2
- 2.Cable Type:Duplex Ø2 OM4 50/125 LSZH
- 3.Length: see the chart
- 4.Jacket Color:Purple
- 5.Jacket Material:LSZH
- 6.IL: ≤0.3dB

**OPERATION:**

- Increase in insertion loss after 500 mating:0.2dB Max  
 Operation Temperature:-20°Cto+70°C  
 Storage Temperature:-40°Cto+80°C  
 Humidity(non-condensing)95%RH  
**The bending radius :Cable coil radius can not less than 30mm**

Item No.:	21.99.8770	0.5m
Item No.:	21.99.8771	1.0m
Item No.:	21.99.8772	2.0m
Item No.:	21.99.8773	3.0m
Item No.:	21.99.8775	5.0m
Item No.:	21.99.8778	10.0m

TOLERANCE	± MM	VALUE FO Cable, 50/125, LC-ST, OM4			
X		DRWN	CHKD	APROYED	
X. X		SCALE	UNIT	QTY	PAGE
X. XX			MM	1 PCS	1 OF 1
X. XXX		THIRD ANGLE PROJECTION			
PROVIDER		<b>Rotronic Co., Ltd.</b>			
PART NO.					