

PICCOLO

GRADE 3 INTERNAL SOUNDER

This remotely powered sounder features a piezo sounder and two bright LED's for audible and visual indication. The sound output is selectable for either alternating or continuous tone. It is also protected against tampering by means of lid removal and removal from the mounting surface.



- Grade 3 Environment Class IV
- Low profile design
- 115dB Sound output
- Selectable alternating or continuous tone
- Flashing alarm indication
- Low current consumption
- Tamper protected lid and mounting
- Can be installed in security systems up to and including Grade 3

Piccolo Specifications

Nominal Power Supply:	12v DC	Flash only Current:	17mA @ 12v DC
Voltage Range:	9-15v DC	Sound and Flash:	100mA @ 12v DC
Sounder Type:	Piezo	Temperature Range:	-15°C - +40°C
Sound output level:	115dB(A) @ 1 Metre	Material:	Polycarbonate
Sound only Current:	84mA @ 12v DC	Dimensions:	125mm x 85mm x 37.5mm



Contact us:

Phone:

Tel: +44(0)151 6061000

Fax: +44(0)151 6061122

Online:

Web: www.cqr.co.uk

Email: info@cqr.co.uk



Address: CQR Fire & Security, 125 Pasture Road, Moreton, Wirral, CH46 4TH, UK.

