






HDMI19M



LOGO (Laser):



Electroinc Test:

Insulation Resistance: 10mΩ

Conduction Impedance: 5Ω


High-Pressure Test: 300V

11. 04. 5801	Premium HDMI Ultra HD Cable + Ethernet, M/M, 1m(3ft)
11. 04. 5802	Premium HDMI Ultra HD Cable + Ethernet, M/M, 2m(6ft)
11. 04. 5803	Premium HDMI Ultra HD Cable + Ethernet, M/M, 3m(10ft)
11. 04. 5804	Premium HDMI Ultra HD Cable + Ethernet, M/M, 4.5m(15ft)

Description:

- Cable UL20276 (26AWG*1P+AL+D+M)*5C+26AWG*4C+M+AL+D+B, OD=8.5mm, Color: Black
- Braid 1/2 Black+1/2 Transparent PET Braid
- Connector HDMI 19P, Gold Plated, RoHS
- Solder Lead Free Solder Wire OD=0.8mm, 1000G
- Tube φ1.0 RoHS
- Tube φ3.0mm RoHS
- Inner mold LD-PE 950 PE RoHS
- Mask 1.8cm RoHS
- Copper foil 2.2cm RoHS
- Outer mold Black PVC A813 45P RoHS
- Metal shell Metal Shell Gold Plated 29*20.5*12.5mm, Laser Mark "PREMIUM", "HDMI"
- Cover HDMI M PE Cover

Pin Out:



REV.	DATE	CONTENTS OF CHANGE	DESIGNER	TOL ±	Plc	Met	Ins	Por	V	Cab	Pac	Gas	DIS	APPROVAL	CHECK	DRAWING	DESIGN	DRAWING NAME	ROLINE Premium HDMI Ultra HD Cable + Ethernet, AM / AM, black
1				RANGE														DATE	
2				0~6	0.1	0.1	0.1	0.2	0.5	1	0.5	0.2		Allen	Allen		Philip	2016-05-6	PART NO. 11.04.5801, 11.04.5802, 11.04.5803, 11.04.5804
3				6~30	0.1	0.1	.15	.25	1	1	0.5	.25							ROO
4				30~80	0.1	.15	0.2	0.3	2	1.5	1	0.3							
5				80~180	.15	.15	.25	0.3	2	2	1	.45							
6				180~315	.15	0.2	0.3	0.4	2.5	2	1	0.6							
7				315~800	0.2	0.3	0.4	0.5	3	3	2	1.1							