



RBF “PPD” POLYPROPYLENE CONDUIT

www.ronbar.co.uk sales@ronbar.co.uk

**HALOGEN
FREE
LOW SMOKE
NFR
NON FLAME
RETARDANT
PROTECTIVE
INSULATING
CORRUGATED
PLIABLE CONDUITS
SYSTEM**

THIS PRODUCT CAN ALSO BE SUPPLIED ON A SPLIT VERSION ADD “SPLIT” AFTER CODE. Please note this will change the IP rating.

THIS PRODUCT CAN ALSO BE SUPPLIED WITH A DRAW WIRE PLEASE ADD “DW” AFTER CODE

APPLICATIONS	DATA INSTALLATIONS
MATERIAL	POLYPROPYLENE
STANDARDS	EN50086.1 EN50086.22 Superseded by EN61386.1 and EN61386.22
COLOUR	BLACK/WHITE standard. RED, YELLOW, GREY & BLUE also available MOQ may apply.
COMPRESSION RESISTANCE	Class 2 = Light 320N on 5cm at 20° C
IMPACT RESISTANCE	Class 2 = Light 1 Joule at 5° C
MINIMUM TEMPERATURE INSTALLATION AND APPLICATION RANGE -5° C MAXIMUM TEMPERATURE INSTALLATION AND APPLICATION RANGE +90° C	

PART No:	TRADE SIZE	OD mm	ID mm	COIL M
PPD7	7	7	4.5	50
PPD10	10	10	6.9	50
PPD12	12	12	10	50
PPD16	16	16	10.7	100
PPD20	20	20	14.1	100
PPD25	25	25	18.2	50/100
PPD32	32	32	24.2	50
PPD40	40	40	32.4	25
PPD50	50	50	41.2	25
PPD63	63	63	54	25

