



OPEN TOP

TOP

NOTES:

ELECTRICAL:

1. VOLTAGE RATING: 125 VAC RMS
2. CURRENT RATING: 1.5AMP
3. CONTACT RESISTANCE: 100MILLIOHMS MAX
4. INSULATION RESISTANCE: 100 MEGOHMS MIN @500 VDC
5. DIELECTRIC STRENGTH: 750 VAC RMS 60Hz, 1MIN

ENVIRONMENTAL:

1. STORAGE: -40°TO+85°
2. OPERATION: 0°TO70°

MECHANICAL:

1. HOUSING MATERIAL: PC BLACK
2. PCB MATERIAL: FR-4 T=1.6MM
3. IDC MATERIAL: PC, CONTACT: PHOSPHOR BRONZE; WITH NICKEL PATING;
4. IDC LIFE: 200 TIMES MIN;

					CO_{Value}TEC					
SYM		Number	Bill No.of Alteration	Signature	Date	Material			Item No.	21.99.3048
Angles Projection						Size	Scale	Unit	DWG No.	UTP-00-01
Drawn	Ding jian bo	2015.12.28	Tolerance			A4	X:1	mm	Part Name	VALUE Cat.6a UTP Junction Box
Checked	Ge pei jun	2015.12.28	0.00-20.00	±0.10					ERP	Part No.
Approved	Wang wei jun	2015.12.28	20.00-50.00	±0.15						
			50.00-100.00	±0.20	Sheet	1 OF 1	Version:	A/0		
			100.00-	±0.25						
			Angle	±30°						