

Tel: 0845 094 0244

Fax: 0845 094 0255

www.securiflex.co.uk

sales@securiflex.co.uk

SFX/SPK-SS-2C-2.5-LSZH-BLK	
Speaker Cable Secure Sound 2 Core OFC 2.5mm Round Black LSZH	
Cable Construction	2 Cores
Conductor	Bare Copper
Conductor Diameter (mm)	0.25 ±0.008 × 50
Insulation	LSZH
Insulation Thickness (mm)	0.48
Insulation Diameter (mm)	3.00 ±0.15
Insulation Colours	Red,Black
Filler	Chalk
Jacket	LSZH
Jacket Thickness (mm)	0.80 ±0.01
Overall Diameter (mm)	10.00 ±0.20
Jacket Colour	Black RAL 9005
Sheath Printing	Secure Sound 2C 2.5mm OFC Speaker LSZH RoHS2 (PO) (m)
Reaction to Fire	Fca
Electrical Characteristics	
Max Conductor DC resistance @ 20°C	<8Ω/km
Rated Temperature	70°C
Rated Voltage	30V
Insulation Resistance @20°C	>200MΩ/km



Every care is taken to ensure all information in this publication is correct. No Legal responsibility can be accepted for any inaccuracy. The company reserves the right to alter or modify the information of this specification without notice. E&OE. Registered in England & Wales, Company No.03758330. VAT Number: 736 5084 24