



## THE INDUSTRY'S MOST TRUSTED CABLE BRAND

SFX/SPK-PRO-2C-PE-BLK

Speaker Cable 2 Core BC 30x0.25mm 16AWG Black PE



Cable Construction	
Cable Construction	2 Cores
Conductor	Bare Copper
Conductor Diameter (mm)	0.25 ±0.008 x 30
Insulation	
Insulation	LSZH
Insulation Thickness (mm)	0.31
Insulation Diameter (mm)	2.25 ±0.10
Insulation Colours	Red,Black
Filler	Cotton Rope
Jacket	PE
Jacket Thickness (mm)	0.60 ±0.01
Overall Diameter (mm)	6.20 ±0.20
Jacket Colour	Black RAL 9005
Sheath Printing	Secure Sound 2C 1.5mm Speaker PE RoHS2 (PO) (m)
Reaction to Fire	Fca
Electrical Characteristics	
Max Conductor DC resistance @ 20°C	<12.6Ω/km
Rated Temperature	80°C
Rated Voltage	30V
Insulation Resistance @20°C	>200MΩ/km



[www.sfxcables.co.uk](http://www.sfxcables.co.uk)

Every care is taken to ensure all information in this publication is correct. No Legal responsibility can be accepted for any inaccuracy.  
The company reserves the right to alter or modify the information of this specification without notice. E&OE.