



## THE INDUSTRY'S MOST TRUSTED CABLE BRAND

SFX/SPK-PRO-2C-LSZH-PNK

Speaker Cable 2 Core BC 30x0.25mm 16AWG Pink LSZH



<b>Cable Construction</b>	2 Cores
Conductor	Bare Copper
Conductor Diameter (mm)	0.25 ±0.008 x 30
<b>Insulation</b>	LSZH
Insulation Thickness (mm)	0.31
Insulation Diameter (mm)	2.25 ±0.10
Insulation Colours	Red,Black
Filler	Cotton Rope
<b>Jacket</b>	LSZH
Jacket Thickness (mm)	0.60 ±0.01
Overall Diameter (mm)	6.20 ±0.20
Jacket Colour	Pink RAL 3015
Sheath Printing	Secure Sound 2C 1.5mm Speaker LSZH RoHS2 (PO) (m)
Reaction to Fire	Fca
<b>Electrical Characteristics</b>	
Max Conductor DC resistance @ 20°C	<12.6Ω/km
Rated Temperature	70°C
Rated Voltage	30V
Insulation Resistance @20°C	>200MΩ/km



[www.sfxcables.co.uk](http://www.sfxcables.co.uk)

Every care is taken to ensure all information in this publication is correct. No Legal responsibility can be accepted for any inaccuracy. The company reserves the right to alter or modify the information of this specification without notice. E&OE.