



SMOKE SCREEN INTERFACE

OPERATING INSTRUCTIONS



NORMAL OPERATION

- Green 'System Ready' LED illuminated.
- Keyswitch - turned to 'Ready'.

USER ACTION

- Nil.

FAULT CONDITIONS

- Panel buzzing.
- Green 'System Ready' LED not illuminated.

USER ACTION

- Call 01205 821111.
- Panel buzzing.
- Red 'Low Fluid' LED illuminated.
- Change smoke consumable.
- Order replacement consumable.

ACTIONS AFTER ALL SMOKE SCREEN ACTIVATIONS

- Wait until the system has completed its pre-set operating period and that smoke production has ceased. Do not try and enter the affected area.
- Look for obvious signs of forced entry. If there are any or if you believe criminals are on the premises wait for the Police to arrive. Take no further action.
- Where there are no signs of forced entry, open external doors and wait as the smoke starts to vent - this may take 10 to 15 minutes. Keep watch for intruders who may have hidden in the smoke.
- As visibility returns you can open more doors and windows to speed up venting.
- Check the fluid for the Smoke Screen units.

IMPORTANT INFORMATION - SMOKE FLUID

Only Smoke Screen Fluid should be used otherwise damage may occur and noxious fumes emitted. Always ensure that the Smoke Screen has sufficient fluid.

CAN'T SEE IT? CAN'T STEAL IT!