

Ei630iRF

RadioLINK+ Heat Alarm



- Heat sensor - responds to heat build-up from large flaming fires (triggers at 58°C)
- AudioLINK+ data extraction technology
- 10 year Lithium battery powered
- RadioLINK+ Wireless interconnection
- Kitemarked to BS 5446-2:2003
- 5 year guarantee



Kitchen



Garage



Description

The Ei630iRF RadioLINK+ Heat Alarm is powered by a 10 year life sealed in Lithium cell. It is able to wirelessly interconnect with any other RadioLINK products and also features a large test button and twist on base with an anti-tamper locking option

Technical

Sensor Type	Heat (AI)	RF Frequency (MHz)	868.499
RF Range (m)	>100 in free air	Indicators	Red - Power Up, Alarm, Silence Mode, Fault / Blue - RF transmission
Battery Type	Lithium primary	Technologies	AudioLINK+ / RadioLINK+

Dimensions & Weights

Depth (mm)	64	Height (mm)	120
Width (mm)	120	Product weight (kg)	0.206
Packaged weight (kg)	0.276		

Approvals & Warranty

Certification/Approvals	BS 5446-2:2003 / EN 300 220-1 / EN 301 489-1	Warranty	5 year warranty
EAN Number	5099383010275		

Environmental

Humidity Range (%)	15-95	Temperature Range (°C)	-10 to 40
---------------------------	-------	-------------------------------	-----------