

PoE Tester

KÄUDEN®

Features :

- Very Compact Size, Easy to Carry, Low Cost.
- Detects Popular Power Over Ethernet Standards.

Specifications:

PoE Detection	IEEE 802.3af/at/bt, 48V, 24V Passive Mode A, Mode B, Mode C
PoE Input (RJ45)	21--27V DC, 42--57DC
Compatible Port Speed	10/100MB/1000MB
LED	Dual Color (Red / Green)
Operating Temperature	-25 to +50°C (-13 to +122°F)
Operating Humidity	5% - 90% non-condensing
Storage Temperature	-40 to +80°C (-40 to +176°F)
Dimensions (LxWxH)	71.3*22*21.2mm
Weight	18g



LED indicators:

LED Indicators	Bright Colors	PoE Standard	Pin
LED A	Red	802.3 af PoE or 48V passive	Pins 4,5,7and 8
	Green	802.3 at PoE+	
LED B	Red	802.3 af PoE or 48V passive	Pins 1,2,3and 6
	Green	802.3 at PoE+	
LED A&B	Both Red	802.3af PoE	All pins
	Both Green	802.3 bt PoE+ +	
LED C	Red	24V passive	Pins 4,5,7and 8

Description:

The PoE -Tester is a new generation of easy-to-use PoE detection adapter, suitable for network installers, system integrators, company management information systems and even home users to quickly identify the existence of Power over Ethernet on application network. It is designed to detect whether IEEE 802.3af/at/bt and 24V voltage are running on the cable, and to identify the type of PSE (power supply equipment). This product has a compact design and is tailor-made for system integrators and installers.

The PoE tester detects 48V output through mode A and mode B, and detects 24V output through mode C. Mode A (supplied on pins 4, 5, 7, 8), Mode B (supplied on pins 1, 2, 3, 6), Mode C 24V (supplied on pins 4, 5, 7, 8).

