

LEDPROSLB

Dedicated PIR Detector for LEDPRO Floodlights - Black

Features & Benefits

- Dedicated PIR for use with Timeguard LEDPRO floodlights
- 2x cable entries suitable for PG11 gland (glands not supplied)
- Fits ALL Timeguard LEDPRO floodlights
- Simply replaces the terminal cover and plugs in to the LEDPRO floodlight – no extra cabling necessary
- Installer friendly captive terminal cover screws
- Tilt and rotate adjustable head for accurate reliable detection
- Photocell sensor (Adjustable) and manual override function complete with masking kit



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Plug-in (LEDPRO Module)
Earth Class Rating	Class I
Ingress Protection Rating	IP55
Setting Type	Dial
Approved Mounting Height (m)	2.5
Motion Detection (m)	12
Detection Angle	180°
Pan & Tilt Adjustment	Pan Left 90°, Pan Right 90°. Tilt Down 150°

Data sheet

LEDPROSLB

Light / LEDPRO Lighting

Standby Consumption	<1W
Switch rating	250W LED, 1000W Halogen, 200W CFL, 500W Fluorescent Tube w/o PF Correction
ON Time Adjustment	3 Seconds to 18 Minutes
Lux Level	2 to 1000
Detection Range (M)	12
Permanent ON Facility	Yes (Pulse Override)
Multiple Unit Support	Yes
Cable Entry(s)	Back Entry

General

Weight (g)	124
Height (mm)	114
Width (mm)	78
Depth (mm)	108
Body Construction	Polycarbonate
Product Colour	Black
EAN Number	5012483013779
Guarantee Period	3 Years
Trade Tariff Commodity Code	8536508090

Data sheet

LEDPROSLB

Light / LEDPRO Lighting

Line Diagrams

