

BatteryCam2

Upgrade security peace-of-mind with BatteryCam2

Enjoy vivid colour surveillance day and night with the fully wireless BatteryCam2. With easy installation using magnetic or bracket mounts, continuous power via *SolarPanel2, *32GB micro SD storage, reliable IP65 weatherproofing, onboard siren and white light for enhanced deterrence, our newest Wi-Fi camera is ideal for effective internal and external security solutions.

Vivid colour surveillance, with added deterrence.



BatteryCam2

Partcode	BATTERY/CAM2
Camera	
Image Sensor	1/2.9" 3 Megapixel CMOS
Effective pixels	2304(H) x 1296(V)
Shutter	1/15~1/10,000s
Min Luminance	Colour 0.1 Lux@F2.0, Black/White 0.01 Lux@F2.0
IR distance	Night visibility up to 10m
Day/Night	Auto(ICR)/Colour/B&W
WDR	DWDR
Lens	3.2mm@F2.0, 130°
Video & Audio	
Compression	H.264
Bit rate	32Kbps~2Mbps
Frame rate	1~25fps
Dual stream	Yes
Audio input/output	Built-in mic/speaker
Network	
Alarm trigger	PIR human-body detection
Communication protocol	HTTP, DHCP, DNS, TCP/IP
Interface protocol	Private
Wireless	2.4G WIFI (IEEE802.11b/g/n)
Security	AES128
Wireless security	64/128-bit WPA/WPA2, WPA-PSK/WPA2-PSK, WPS
Max user access	4
Battery & PIR	
Capacity	9600mAh rechargeable Li batteries
Stand-by current	200-800 μ A (average)
Working current	150-200 mA (IR off)
Stand-by time	6 months
Working time	2-3 months (varies based on settings, usage & temperature)
PIR detection range	Max. 9m
PIR angle	120°
General	
Operating temperature	-20°C to 50°C
IP rating	IP65
Power supply	DC 5V/1A
Power consumption	Max. 2W
*Optional accessory	SolarPanel2 32GB SD card
Storage	SD card (Max.128GB)
Dimensions (W x H x D)	57 x 63 x 100mm
Net weight	235g

*Both available in a kit, along with the BatteryCam2.

Flexible installation options

With a magnetic bracket and screw-in bracket both included, there are more installation options than before, ensuring rapid and hassle-free fitting.

The strongly magnetised "ball and socket" type of bracket enables the camera to be quickly positioned in place and removed for charging. It also allows easy fine-tuning of the camera viewing angle, whilst the screw-in bracket provides even more dexterity in camera angle adjustment.

High definition, vivid imagery

Access high quality footage through the HomeControl2.0 app, with an upgraded 3MP image sensor. The new, inbuilt white light means that the camera streams in full colour when activated, no matter the time of day.

Perfecting perimeter and porch protection

With the onboard light acting as an intruder deterrent or a courtesy light alongside the onboard siren that can trigger upon detection of an intruder, the BatteryCam2 is ideal for protecting property boundaries, driveways, garages and porches, or simply for welcoming owners home.

Adjustable detection zone

Using HomeControl2.0, homeowners can select a specific area within the camera's view which will be monitored to trigger events; ensuring that users only receive alerts when it matters.



Follow us on LinkedIn  @pyronixltd 

www.facebook.com/pyronix  @pyronix 

Pyronix Limited, Secure House, Braithwell Way, Hellaby, Rotherham, South Yorkshire, S66 8QY, UK

T: +44 (0)1709 700 100 E: sales@pyronix.com W: www.pyronix.com