

EURO 46 V10



One panel, versatile security

Future-proof your installations. It's time to streamline your security.

No longer will you fit a panel dependent on the communication preference, instead, fit a panel and then add the communicator required. With HomeControl+ App compatibility as standard (with optional IP communicator) you can offer greater value and future-proof your installations. The same programming you have come to love, the same accessories, just less hassle and greater up-sell opportunities.

 www.facebook.com/pyronix

 [@pyronix](https://twitter.com/pyronix)

 Follow us on LinkedIn

Pyronix Limited, Secure House, Braithwell Way, Hellaby, Rotherham, South Yorkshire, S66 8QY, UK
T: +44 (0)1709 700 100 E: sales@pyronix.com W: www.pyronix.com

EURO 46 V10



| | | |
|----------|-------------|-------------|
| Partcode | EURO46S V10 | EURO46L V10 |
|----------|-------------|-------------|

EURO kit contents

| | Small | Large |
|-------------------------------------|---|---|
| Metal casing with tamper protection | Small | Large |
| PCB | ✓ | ✓ |
| Power supply | ✓ | ✓ |
| Keypad (EUR-064) | ✓ | ✓ |
| Communication modem | Not included (Compatible with PSTN, PSNT-Voice, GSM, WIFI, LAN, GPRS) | Not included (Compatible with PSTN, PSTN-Voice, GSM, WIFI, LAN, GPRS) |

Key features

| | |
|-------------------------------------|--|
| Independent areas or levels | 6 |
| Wired inputs (NC/DEOL) | 8 (76) |
| Two-way wireless inputs | 0 (64) |
| Outputs on board | 5 expandable to 75 |
| ATE outputs on board | 10 |
| Expanders (max) | Wired input (ZEM8) x 8, Wireless input (ZEM32-WE) x2, Wired output x2 |
| Keypads | 6 (wired) 4 (wireless arming station with ZEM32-WE) |
| Log events | 1250 |
| Two-way wireless keyfobs (max) | 0 (32) |
| User codes and prox tags | 75 |
| Guard codes | 10 |
| Two-way wireless sounders | 2 (with 2 x ZEM32-WE) |
| Phone numbers for SMS notification | 10 |
| Reporting formats | PSTN (Fast Format, ContactID, SIA, SIA 3, SMS (Tap)) GSM (SMS) WiFi & LAN (SIA IP, Contact ID IP, Fast Format IP, Cloud/App) GPRS (SIA IP, Contact ID IP, Fast Format IP, Cloud/App, SMS), WebWayOne, Chiron |
| Compatibility with HomeControl+ App | ✓ |

Technical specifications

| | Small | Large |
|---|-------------------------------------|-------------------------------------|
| Internal power supply | 1.5A | 2A |
| Power supply | 110-230VDC / 50-60 Hz | 110-230VDC / 50-60 Hz |
| Current consumption | 80mA | 80mA |
| AUX output voltage | 9 - 16 DC (12 DC normal) | 9 - 16 DC (12 DC normal) |
| Programmable outputs | 3A, Max 30V relay | 3A, Max 30V relay |
| Siren and strobe output | 500mA | 500mA |
| Default input resistors (additional optional resistor values are available) | 4k7 (alarm) 2k2 (tamper) 6k8 (mask) | 4k7 (alarm) 2k2 (tamper) 6k8 (mask) |
| Battery capacity | 3 - 7Ah | 3 - 17Ah |
| AUX fuse | 800mA | 800mA |
| Siren fuse | 800mA | 800mA |

Other details

| | | |
|---------------------------------|-------------------------------|-------------------------------|
| Operating storage temperature | -10°C / +50°C -20°C / +60°C | -10°C / +50°C -20°C / +60°C |
| Dimensions (W x H x D) | 250 x 297 x 82mm | 305 x 390 x 100mm |
| Weight | 3.6 kg | 5.6 kg |
| Warranty | 2 years | 2 years |

Certifications

| | | |
|-----------------------|---------|---------|
| Electrical conformity | CE | CE |
| EN50131 | Grade 2 | Grade 3 |
| Environmental class | II | II |

*smartphone not included. Pyronix reserves the right to change product descriptions and specifications without prior notice.