



TITLE:

FR30 Fire Standard

CODE:

SFX/FC-3C-1.5-FR60-STD-RED-100

DESCRIPTION:

100m 3 Core 1.5mm 300/500V Red Standard FLAME-FLEX 60

SUPPLIED AS:

Reel of 100m

- Can be used both internally and externally in environments where suitable protection is present
- Polymer tape comes away from the sheath when stripping cable
- Low smoke zero halogen plastic is good for use inside public buildings and spaces as will not emit toxic gases if the cable catches fire
- Can be used for emergency lighting applications
- Suitable for installations where a circuit must be maintained for up to 60 minutes in the event of a fire
- Various lengths in stock



enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23



Product Specification

25-YEAR WARRANTY

Cable Construction

Cable Construction	3 Cores
CPR	LPCB
Conductor	Solid Bare Copper
Overall Diameter (mm)	8.30 ±0.01

Insulation

Insulation	Silicon Rubber
Insulation Colour	Brown,Black Grey
Insulation Thickness (mm)	0.70 ±0.02

Outer/Jacket Specification

Jacket	LSZH
Overall Colour	Red
Overall Diameter (mm)	8.30 ±0.01
Jacket Colour	Red RAL 3000
Jacket Thickness (mm)	0.70 ±0.01

Electrical Characteristics

Rated Temperature (°C)	-30°C - +40°C to 70°C
Rated Voltage (V)	300/500V



enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23



MORE INFORMATION:

Sorry, no more information is available for this product

Fire cable



enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23