


SFX/ISP3-SWA-PE-BLK

ISP3 3pr 22AWG Individual Foil Screen 600V SWA Black PE (8777)



Cable Construction	3 Pairs
Conductor	Tinned Copper
Conductor Diameter (mm)	0.24 ±0.008 x 7(0.33mm ²)
Stranded Diameter (mm)	0.64
Insulation	HDPE
Insulation Thickness (mm)	0.28
Insulation Diameter (mm)	1.20 ±0.10
Insulation Colours	Red,Black;Green,Black;White,Black
Drain Wire	Each pair is twisted with Individual drain wire inside it's own Al PET-Shield
Conductor	Tinned Copper
Conductor Diameter (mm)	0.24 ±0.008 x 7
Al-PET Shield	≥115% (On each pair)
Mylar Spiral	≥115% (On each pair)
Nylon Rip-Cord	White 210D
Inner Jacket	PE
Inner Jacket Thickness (mm)	1.0
Inner Diameter (mm)	7.20 ±0.20
Inner Jacket Colour	Black RAL 9005
Armour	Galvanized Steel Wire
Armour Construction (mm)	0.90 x 25
Outer Jacket	PE
Outer Jacket Thickness (mm)	1.20
Overall Diameter (mm)	11.40 ±0.20
Outer Jacket Colour	Black RAL 9005
Sheath Printing	ISP3 3x2x22AWG 600V Individually Screened SWA PE RoHS2 (PO) (m)
Reaction to Fire	Fca
Electrical Characteristics	
Max Conductor DC resistance @ 20°C	<50Ω/km
Rated Temperature	80°C
Rated Voltage	600V
Insulation Resistance @20°C	>200MΩ/km
Standards	CE2014/30/EU, RoHS2 2011/65/EU, LVD 2014/35/EU
Application	Audio, control and Instrumentation.