


SFX/OSP1-62-LSZH-GRY

OSP1-62 1pr 20AWG Overall Foil Screen Grey LSZH 600V (8762) CPR:Eca



<b>Cable Construction</b>	1 Pair
Conductor	Tinned Copper
Conductor Diameter (mm)	7 x 0.28
Stranded Diameter (mm)	0.56
<b>Insulation</b>	HDPE
Insulation Thickness (mm)	0.430
Insulation Diameter (mm)	1.80 ±0.10
Insulation Colour(s)	Black, Clear
<b>Al-PET Shield</b>	≥115%
<b>Drain Wire</b>	
Drain Wire Conductor	Tinned Copper
Drain Wire Conductor Diameter (mm)	7 x 0.28
<b>Jacket</b>	LSZH
Jacket Thickness (mm)	0.70
Overall Diameter (mm)	5.00 ±0.20
Jacket Colour	Grey RAL 7042
Sheath Printing	OSP1-62 2x20AWG Overall Screened LSZH RoHS2 (PO) (m)
Reaction to Fire	Eca
<b>Electrical Characteristics</b>	
Max Conductor DC resistance @ 20°C	<37.00Ω/km
Rated Temperature (°C)	-40°C to 70°C
Rated Voltage (V)	600V
Insulation Resistance @20°C	>200MΩ/km
Standards	CE2014/30/EU, RoHS2 2011/65/EU, LVD 2014/35/EU
Application	Audio, control, instrumentation and panel wiring.