

SFX/OFB2-LSZH-GRY

OFB2 2pr 24AWG Overall Foil and Braid Screen 600V Grey LSZH (9842)



Cable Construction	2 Pairs
Conductor	Tinned Copper
Conductor Diameter (mm)	0.19 ±0.008 x 8
Stranded Diameter (mm)	0.6
Insulation	HDPE
Insulation Thickness (mm)	0.55
Insulation Diameter (mm)	1.83 ±0.10
Insulation Colours	White/Blue,Blue;White/Orange,Orange
Al-PET Shield	>=115%
Drain Wire	
Conductor	Tinned Copper
Conductor Diameter (mm)	0.19 ±0.008 x 7
Braid	Tinned Copper
Braid Construction	0.11 ±0.008 x 128 ±2
Braid Coverage	>=90%
Nylon Rip-Cord	150D
Jacket	LSZH
Jacket Thickness (mm)	0.8
Overall Diameter (mm)	8.65 ±0.20
Jacket Colour	Grey RAL 7042
Sheath Printing	OFB2 2x2x24AWG 600V Foil & Braid Screen LSZH RoHS2 (PO) (m)
Reaction to Fire	Eca
Electrical Characteristics	
Max Conductor DC resistance @ 20°C	<83Ω/km
Rated Temperature	70°C
Rated Voltage	600V
Insulation Resistance @20°C	>200MΩ/km